

CA178



RF Cable Assembly 700MHz to 5.825GHz

The CA178 cable assemblies offered by Laird Technologies are engineered for peak performance up to 6GHz. They are tested 100% and certified to meet performance specifications. Equipment manufacturers require certified cable assemblies to minimize system losses to within known parameters and these cable assemblies meet those requirements. The manufacturing processes and raw materials are well controlled in order to provide very consistent performance from lot to lot.

Features and Benefits:

- Consistent low loss design construction
- 100% tested and certified to meet specifications
- Various connector options available
- Flexible high temperature kink resistant cable jacket

Applications

- High performance wireless systems
- OEM Equipment

For sales information: Telephone 801-572-3024 F-Mail sales@nacwireless.co

or visit: www.pacwireless.com





CA178

Specifications

Part #	CA178-NFB-UFL-8	CA178-NFB-UFL-12
Insertion Loss (700-5825MHz)	-1.5dB Max	-2.5dB Max
Length	8" (203 mm)	12" (305 mm)
Weight	1.4oz (40gm)	1.5oz (43gm)
Connector Types	N Female Bulkhead - UFL	N Female Bulkhead - U.fl
N Connector Seal	O-Ring	O-Ring
Contact Plating	Gold	Gold
Operating Temperature	-40 deg C to +125 deg C	-40 deg C to +125 deg C

Insertion Loss By Frequency





System Ordering:

- CA178-NFB-UFL-8 : N Female Bulkhead to U.FL 8"
- CA178-NFB-UFL-12 : N Female Bulkhead to U.FL 12"
- CA178-NM-UFL-8 : N Male to U.FL 8"
- CA178-NM-UFL-12 : N Male to U.FL 12"

Notes:

- All shipments F.O.B. Schaumburg, IL 60173
- All antennas carry a 2 Year Warranty



Any information furnished by Laird Technologies and its agents is believed to be accurate and reliable. Responsibility for the use and application of Laird Technologies materials rests with the end user since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability, or suitability of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies domestic terms and conditions of sale in effect from time to time, a copy of which will be furnished upon request.

Specifications subject to change without notice.

global solutions : local support_™